

SAFETY DATA SHEET

Butane Battery® Butane Cartridge

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Butane Battery® Butane Cartridge

Chemical name Hydrocarbons, C3-4-rich, petroleum distillate

Product number D2, D4, P2, S4, S6, A4

Synonyms; trade names Petroleum gas

CAS number 68512-91-4

EU index number 649-083-00-0

EC number 270-990-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel for portable gas appliances.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Go Gas Ltd

Unit 1B, East Tame Business Park

Newton Hyde Cheshire

SK14 4GX Tel: 0161 3671315 Fax: 0161 367 1316

info@gogas.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 161 3671315 (Mon - Fri, 0900 - 1700)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Gas 1 - H220 Press. Gas, Liquefied - H280

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

EC number 270-990-9

Pictogram





Butane Battery® Butane Cartridge

Signal word Danger

Hazard statements H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place. P412 Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product name Butane Battery® Butane Cartridge

Chemical name Hydrocarbons, C3-4-rich, petroleum distillate

EU index number 649-083-00-0

CAS number 68512-91-4

EC number 270-990-9

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel. Keep affected person away from heat, sparks and flames.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. When breathing is difficult, properly trained personnel may assist

affected person by administering oxygen.

In the event of an incident leading to contact with the liquid contents: Remove person to fresh

air and keep comfortable for breathing. Rinse mouth thoroughly with water. Get medical

advice/attention if you feel unwell.

Skin contact In the event of an incident leading to contact with the liquid contents: Rinse with water. Thaw

frosted parts with lukewarm water. Do not rub affected area.

Eye contact In the event of an incident leading to contact with the liquid contents: Rinse with water. Get

medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation No specific symptoms known. Overexposure may cause the following adverse effects:

Drowsiness, dizziness, disorientation, vertigo.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact No specific symptoms known. In the event of an incident leading to contact with the liquid

contents: Contact with liquid form may cause frostbite.

Eye contact No specific symptoms known. In the event of an incident leading to contact with the liquid

contents: Contact with liquid form may cause frostbite.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.

Vapours may accumulate on the floor and in low-lying areas. Vapours may form explosive

mixtures with air.

Hazardous combustion products

Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. If involved in a fire, shut off flow if it can be done without risk. Large fires: Allow fire to burn out. Small fires: Fight fire remotely due to the risk of explosion. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsWear protective clothing as described in Section 8 of this safety data sheet. No action shall be

taken without appropriate training or involving any personal risk. Evacuate area. Vapours may form explosive mixtures with air. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that

becomes contaminated.

6.2. Environmental precautions

Environmental precautions Exposure to aquatic environment unlikely.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions May damage fertility. Suspected of damaging the unborn child. Suspected of damaging

fertility. Suspected of damaging the unborn child. Suspected of damaging the unborn child.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash

contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep

away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect

containers from damage. Protect from sunlight.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering

Provide adequate ventilation.

controls

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard

should be worn if a risk assessment indicates eye contact is possible.

Hand protection

Eye/face protection

No specific requirements are anticipated under normal conditions of use. In the event of an

incident leading to contact with the liquid contents: Wear protective gloves.

Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

Wash contaminated clothing before reuse.

Respiratory protection

No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is

inadequate, suitable respiratory protection must be worn.

Environmental exposure

controls

Keep container tightly sealed when not in use. Avoid release to the environment.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Gas.

Colour Colourless.

Odour Characteristic. Hydrocarbons.

pH Not relevant.Melting point Not relevant.

Initial boiling point and range -42°C @ 768 mm Hg

Flash point < -60°C

Evaporation rate Not determined.

Flammability (solid, gas) Flammable Gas

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 3 % Upper flammable/explosive limit: 12.5 % Estimated

value

Vapour pressure 414 kPa @ 20°C

Vapour density 2.07 (butanes) 1.56 (propane)

Bulk density ~ 500 kg/m³

Solubility(ies) Not relevant.

Partition coefficient log Pow: 1.09

Auto-ignition temperature 537°C

Decomposition Temperature Not known.

Viscosity Not relevant.

Explosive properties Vapours may form explosive mixtures with air.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising

properties.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up.

Butane Battery® Butane Cartridge

10.5. Incompatible materials

Materials to avoid Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Not regarded as a health hazard under current legislation.

Acute toxicity - oral

Notes (oral LD₅₀) Not relevant.

Acute toxicity - dermal

Notes (dermal LD50) Not relevant.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ 1443 mg/l, Inhalation, Rat REACH dossier information. Based on available data the

classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Human skin model test Not irritating. Contact with liquid form may cause frostbite.

Serious eye damage/irritation

Serious eye damage/irritation No information available.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation No information available.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Based on available data the

classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available data the

classification criteria are not met.

Carcinogenicity

Carcinogenicity NOAEL 10000 ppm, Inhalation, Mouse REACH dossier information. Based on available data

the classification criteria are not met.

IARC carcinogenicityNone of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEC 10000 ppm, Inhalation, Rat P REACH dossier information. Based on

available data the classification criteria are not met.

Reproductive toxicity -

Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier information.

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Butane Battery® Butane Cartridge

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 10000 ppm, Inhalation, Rat REACH dossier information. Not classified as a specific

target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant. Gas.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation No specific symptoms known. Overexposure may cause the following adverse effects:

Drowsiness, dizziness, disorientation, vertigo.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact No specific symptoms known. In the event of an incident leading to contact with the liquid

contents: Contact with liquid form may cause frostbite.

Eye contact No specific symptoms known. In the event of an incident leading to contact with the liquid

contents: Contact with liquid form may cause frostbite.

Route of entry Inhalation Skin and/or eye contact

SECTION 12: Ecological Information

12.1. Toxicity

Target organs

Toxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

No specific target organs known.

Acute toxicity - fish LC₅₀, 96 hours: 49.47 mg/l, Fish, Estimated value.

Acute toxicity - aquatic

invertebrates

LC₅₀, 48 hours: 16.33 mg/l, Estimated value.

12.2. Persistence and degradability

Persistence and degradability The product is readily biodegradable.

Phototransformation Water - Degradation : 1906 days

Biodegradation Water - Degradation (100%): 385.5 hours

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient log Pow: 1.09

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and

its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section. As supplied, this product is consigned

under the Limited Quantities provisions.

Air transport notes As supplied not packaged suitably for air.

14.1. UN number

UN No. (ADR/RID) 2037

UN No. (IMDG) 2037

UN No. (ICAO) 2037

UN No. (ADN) 2037

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

Proper shipping name (IMDG) RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

Proper shipping name (ICAO) RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

Proper shipping name (ADN) RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group Not relevant.

Butane Battery® Butane Cartridge

IMDG packing group

ICAO packing group

Not relevant.

ADN packing group

Not relevant.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

ADR transport category 3

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not relevant.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Other Regulations Does not contain additives identified as being potentially nano (silica, titanium dioxide, gold,

silver) or ingredients containing these additives.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms LC50 - Median Lethal Concentration

used in the safety data sheet LD50 - Median Lethal Dose

NOAEC - No Observed Adverse Effect Concentration

EC50 - Half maximal Effective Concentration PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent, Very Bioaccumulative

General information Product is labelled as per regulation (EC) 1272/2008, Annex I Section 1.3.2, regarding LPG

products. Compliant with EN417.

Butane Battery® Butane Cartridge

Classification procedures according to Regulation (EC)

Flam. Gas 1 - H220, Press. Gas, Liquefied - H280: Expert judgement.

1272/2008

Training advice Read and follow manufacturer's recommendations.

Revision comments Data sheet reviewed.

Revision date 05/09/2016

Revision 2

Supersedes date 01/06/2013

SDS number 4857

Hazard statements in full H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.